

COMPACT TRACTORS | 25 HP - 42 HP

# MT2E | MT2 SERIES



**LS** Tractor  
Start Blue. Stay Blue.

**MT2E | MT2 SERIES**

# HIGHER STANDARDS. LOWER ISSUES.

Maintaining your land to your standards takes a tractor and attachments made to ours. And with a six-year limited powertrain warranty on most models, you'll be well taken care of as well.



## RECOMMENDED IMPLEMENTS / ATTACHMENTS



### LOADER

High capacity with an abundance of standard features



### BACKHOE

Excellent capacity, smooth and consistent operation for added control



### ROTARY CUTTER

Durable heavy steel design providing quality and strength



### BOX BLADE

Features a heavy welded steel design for use in demanding applications



### NEW LS FAMILY LOOK

Upgraded, modern look also provides better functionality



### LED LIGHTS

Increased visibility while increasing efficiency



### LARGER TIRE SIZE AND OPTIONS

Enhanced traction and stability with more options



### BETTER VISIBILITY

Cab redesign allows for better operator visibility



### LOADER LIFT CAPACITY INCREASE

Do more work easily



### TF-LCD PANEL

Shows regen time, oil change intervals and more



### IMPROVED SEAT COMFORT

So you can stay more comfortable for longer



### UPGRADED ERGONOMIC CONTROLS

Refined controls make for easier operation



### NEW DEEP SKY BLUE PAINT

Elevated look with silver rims

# MT2E / MT2

# SPECIFICATIONS

MODEL	MT226ED	MT226E	MT226E	MT232E	MT232E	MT242E	MT242E	MT226E	MT232E	MT242E	MT232	MT242	MT226	MT232	MT242
<b>Type</b>	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	ROPS Type	Cabin Type	Cabin Type	Cabin Type	ROPS Type	ROPS Type	Cabin Type	Cabin Type	Cabin Type
<b>ENGINE</b>															
<b>Type (Liquid-cooled Diesel)</b>	3 Cylinder, NA, IDI	3 Cylinder, NA, IDI	3 Cylinder, NA, IDI	3 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, IDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI	3 Cylinder, NA, DI	3 Cylinder, NA, CRDI	4 Cylinder, NA, CRDI
<b>Model (Tier 4)</b>	MHI S3L2-W463G-TAC	MHI S3L2-W463G-TAC	MHI S3L2-W463G-TAC	YANMAR 3TN-V88C-MLST	YANMAR 3TN-V88C-MLST	YANMAR 4TN-V88C-MLST	YANMAR 4TN-V88C-MLST	YANMAR 3TNV88F-EPLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST	YANMAR 3TNV88F-EPLST	YANMAR 3TNV88C-MLST	YANMAR 4TNV88C-MLST
<b>Engine HP (gross)</b>	24.6	24.6	24.6	31.7	31.7	42.5	24.6	23.9	31.7	42.5	31.7	42.5	23.9	31.7	42.5
<b>PTO (HP)</b>	19.2	19.2	171	28.5	26.2	35.4	34.8	19	26.2	34.8	26.2	34.8	19	26.2	34.8
<b>Rated Speed (rpm)</b>	2,500	2,500	2,500	2,600	2,600	2,600	2,600	2,400	2,600	2,600	2,600	2,600	2,400	2,600	2,600
<b>Displacement (in<sup>3</sup>)</b>	80.4	80.4	80.4	100.2	100.2	133.6	80.4	100.2	100.2	133.6	100.2	133.6	100.2	133.6	133.6
<b>Fuel Tank Capacity (gal.)</b>	10.6	10.6	10.6	10.6	10.6	10.6	10.6	11.4	11.4	11.4	10.6	10.6	11.4	11.4	11.4
<b>Alternator V-A</b>	12V - 50 Amps	12V - 50 Amps	12V - 50 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps	12V - 55 Amps
<b>DRIVE TRAIN</b>															
<b>Transmission</b>	Synchro Shuttle	Synchro Shuttle	HST	Synchro Shuttle	HST	Synchro Shuttle	HST	HST	HST	HST	HST	HST	HST	HST	HST
<b>No. Of Speed</b>	F12 X R12	F12 X R12	3 Ranges	F12 X R12	3 Ranges	F12 X R12	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges	3 Ranges
<b>Brakes</b>	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc	Wet, Multi-disc
<b>Steering</b>	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering	Hydrostatic Power Steering
<b>PTO</b>															
<b>Type</b>	TM Driven	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent	Independent
<b>Rear (rpm)</b>	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)	Standard (540)
<b>HYDRAULIC SYSTEM</b>															
<b>Control System</b>	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position	Position
<b>Implement Pump (gpm)</b>	7.9	7.9	7.1	7.4	6.7	7.4	6.7	6.1	6.7	6.7	7	7	6.1	7	7
<b>Steering Pump (gpm)</b>	4.6	4.6	4.6	5	5	5	5	4.6	5	5	5	5	4.6	5	5
<b>Total Flow (gpm)</b>	12.5	12.5	11.7	12.4	11.7	12.4	11.7	10.7	11.7	11.7	11.7	11.7	10.7	11.7	11.7
<b>Category (Spt Hitch)</b>	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I	CAT I
<b>Hitch Lift Capacity Hitch End (lbs.)</b>	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808	1808
<b>Remote Valves</b>	Option	Option	Option	Option	Option	Option	Option	1pair	1pair	1pair	1pair	1pair	1pair	1pair	1pair
<b>DIMENSION</b>															
<b>Overall Length (Frame To Link, in.)</b>	119	119	119	125	125	125	125	125	125	125	125	125	125	125	125
<b>Overall Width With Tires (in.)</b>	66	66	66	66	66	66	66	66	66	66	66	66	66	66	66
<b>Wheelbase (in.)</b>	66	66	66	69	69	74	74	69	69	74	69	74	69	69	74
<b>Height To Top ROPS (in.)</b>	95	95	95	95	95	95	95	90	90	90	95	95	90	90	90
<b>TIRE SIZE</b>															
<b>Front / Rear Ag</b>	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24	7 - 14 / 11.2 - 24
<b>Front / Rear Industrial</b>	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20
<b>Front / Rear VT</b>	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20	27X8.50-15 / 43X16.00-20
<b>Front / Rear Turf</b>	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20	25X8.50-14 / 41X14.00-20
<b>WEIGHT</b>															
<b>Total Weight w/o Ballast (lbs.)</b>	2963	2985	3007	3166	3210	3250	3294	3609	3677	3761	3254	3338	3649	3721	3805

FRONT END LOADER	LL3001, LL3002	LL3003
<b>MATCHING TRACTOR</b>	MT226E (ROPS, CAB)	MT232E, MT242E, MT232, MT242
<b>Bucket Size (in.)</b>	66	66
<b>Maximum Lift Height (in.)</b>	94.3	94.3
<b>Clearance With Attachment Dump (in.)</b>	67	67
<b>Reach At Maximum Height (in.)</b>	15.4 (ROPS) / 15.8 (Cab)	15.8
<b>Maximum Dump Angle (deg.)</b>	48	48
<b>Maximum Rollback Angle (deg.)</b>	28 (26.03)	28 (26.03)
<b>Digging Depth (in.)</b>	4.8	4.8
<b>Overall Height In Carry Position (in.)</b>	51.2	51.2
<b>Lift Capacity (Bucket Pivot Pin, MAX, Height) (lbs.)</b>	1,599	2,063
<b>Lift Capacity (Pivot pin @ 1.5m) (lbs.)</b>	1,965	2,506
<b>Breakout Force (@ Pivot pin) (lbs.)</b>	2,962	3,723
<b>Approx. Weight (Loader w/o Bucket) (lbs.)</b>	741	741

BACKHOE	LB3001, LB3002
<b>TRACTOR APPLICATION</b>	MT226E (ROPS), MT226E (CAB), MT232E, MT242E, MT232, MT242
<b>Digging Depth, 2ft. Flat Bottom (in.)</b>	94.1
<b>Reach From Centerline Of Swing Pivot (in.)</b>	127.2
<b>Loading Height (in.)</b>	76.2
<b>Swing Arc (deg.)</b>	160
<b>Transport Height (in.)</b>	81.8
<b>Bucket Rotating (deg.)</b>	180
<b>Stabilizer Spread (Down Position) (in.)</b>	67.5
<b>Stabilizer Spread (Up Position) (in.)</b>	50
<b>Bucket Digging Force (lbs.)</b>	3,663

*\*All specs and features are subject to change, and pictures could include optional equipment etc.*

- Additional Equipment**
- Standard Rear Worklight, ROPS and Cab
  - Standard Drawbar

# START BLUE. STAY BLUE.

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com  
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

## LS Tractor

6-year limited warranty.  
See dealer for details.



---

---

---

---